

AirPrime® FX30 Certified Cellular Modems:

All FX30 units ship with DC cable. If customer wants an AC power supply, use PN: PWR-12VDC-1.5A-FX30


 FX30_1103214 3G Global
 75 x 60 x 32 mm

- Carrier-certified modem
- Programmable Yocto Linux
- 3G HSPA w/ 2G FB & GNSS
- USB/Ethernet interface
- Features Sierra WP8548


 FX30S_1103232 3G Global
 75 x 60 x 32 mm

- Carrier-certified modem
- Programmable Yocto Linux
- 3G HSPA w/ 2G FB & GNSS
- USB/RS232 interface
- Features Sierra WP8548


 FX30_1104086 Cat M1/NB-IOT Global
 75 x 60 x 32 mm

- Carrier-certified modem
- Programmable Yocto Linux
- LTE Cat M1/NB-IOT w/ 2G FB & GNSS
- 300 Kbps DL / 375 Kbps UL
- USB/Ethernet interface
- Features Sierra WP7702


 FX30S_1104087 Cat M1/NB-IOT Global
 75 x 60 x 32 mm

- Carrier-certified modem
- Programmable Yocto Linux
- LTE Cat M1/NB-IOT w/ 2G FB & GNSS
- 300 Kbps DL / 375 Kbps UL
- USB/RS232 interface
- Features Sierra WP7702


 FX30S_1104549 (Serial) | FX30_1104548 (Ethernet)
 75 x 60 x 32 mm

- [Octave Enabled](#)
- Carrier-certified modem
- Programmable Yocto Linux
- LTE Cat M1/NB-IOT w/ 2G FB & GNSS
- 300 Kbps DL / 375 Kbps UL
- Serial or Ethernet interface
- Features Sierra WP7702